



Specifications Noxion LED Downlight Slim V2.0 20W 2000lm 120D - 840 Cool White | 225mm - Cutout 200mm - IP44 - Emergency 3H

[View Product](#)

## General Information

|                      |                                                                                   |
|----------------------|-----------------------------------------------------------------------------------|
| SKU                  | 238919                                                                            |
| EAN                  | 8719157015080                                                                     |
| Manufacturer Code    | 8719157015080                                                                     |
| Brand                | Noxion                                                                            |
| Manufacturer Name    | Noxion LED Downlight Slim V2.0 IP44 20W 4000K Cutout Ø200mm Frame Ø225mm w/ EM3HR |
| Budgetlight warranty | 6 Years                                                                           |
| Average Lifetime (h) | 50000                                                                             |

## Technical Information

|                             |                     |
|-----------------------------|---------------------|
| Emergency Lighting          | With Emergency Unit |
| Tiltable                    | No                  |
| Technology                  | LED Integrated      |
| Wattage                     | 20W                 |
| Voltage (V)                 | 220-240             |
| Dimmable                    | Not Dimmable        |
| Colour Code                 | 840 Cool White      |
| Colour temperature (Kelvin) | 4000 Cool White     |
| Colour Rendering (Ra)       | 80-89               |
| Colour of Light             | White               |
| Light Colour Options        | Single Color        |

|                         |                                       |
|-------------------------|---------------------------------------|
| Inclusief Driver        | Yes                                   |
| Beam Angle (degree)     | 120                                   |
| Luminous Flux (Lumen)   | 2000lm                                |
| Lumen per watt          | 100                                   |
| Powerfactor             | >0.90                                 |
| Installation Depth (mm) | 19                                    |
| Unified Glare Rating    | < 28 - for hallways and storage rooms |
| Optische Afdekking      | PC (Polycarbonate)                    |
| Type product            | LED Downlight                         |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 200               |
| IP-rating              | IP44              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Bedrijfstemperatuur    | -20 to +40        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Product Serie          | Slim              |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 26  |
| Diameter (mm) | 225 |

## Why Budgetlight?



Guaranteed **budget prices**



Up to **7 years warranty**

## Sensor Information



**Easy** return process



Long-life **LED solutions**

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|